

SureColor® P9000



Professional 44" large-format 10-color inkjet printer.

Print your legacy — professional 44"-wide printer for photographic, fine art and commercial proofing applications

UltraChrome HDX™ Inks — professional 10-color archival pigment ink set delivers best-in-class color gamut with higher-density blacks for enhanced overall dynamic range, contrast ratio and clarity for both color and black-and-white prints

Exceptional print permanence — Standard Edition printer offers next-generation pigment ink technology with Light Black ink for up to twice the overall print permanence than previous generations¹

Commercial Edition — features an all-new Violet ink for expanded color gamut with up to 99 percent PANTONE® FORMULA GUIDE solid-coated color-matching accuracy, ideal for all commercial and flexographic proofing applications

Remarkable detail — Epson® PrecisionCore® TFP® printhead delivers high print speeds with 360 nozzles per color channel with variable-size ink droplets as small as 3.5 picoliters

Superior connectivity — standard gigabit Ethernet and USB 2.0 along with an optional internal 320GB print server quickly transfers print jobs and frees up workstations; the internal print server includes print queue management and the ability to save and reprint jobs

Designed for use exclusively with Epson cartridges.*



SureColor® P9000

Print

Printing Technology Advanced PrecisionCore TFP 10-channel, drop-on-demand printhead with ink-repelling coating technology Ink Type UltraChrome HDX pigment ink; 11-ink, 10-color Standard Edition ink configuration: C. LC. VM. VLM. Y. LK. LLK. O.

G and PK or MK Commercial Edition ink configuration: C, LC, VM, VLM, Y, LK, V, O,

G and PK or MK Fade Resistance/Print Longevity¹ Color: up to 200 years;

black-and-white: up to 400 years Nozzle Configuration Color and monochrome heads; 360 nozzles x 10

Droplet Technology Smallest droplet size: 3.5 picoliters; Variable Droplet Technology can produce up to three different sizes per line

Maximum Resolution 2880 x 1440 dpi

Printer Speed²

16" x 20" prints from 2:02 to 6:58; normal is 4:16 20" x 30" prints from 3:40 to 12:25; normal is 7:36 40" x 60" prints from 11:15 to 40:05; normal is 24:20

Printer Language/Drivers Epson ESC/P® raster photographic drivers standard

Auto-switching Black Ink Technology³

Black Ink Conversion Times

Matte to Photo Black: approx. 2:55 Photo to Matte Black: approx. 2:07

Ink Used During Conversion

Matte to Photo Black: approx 7.2 ml Photo to Matte Black: approx. 1.12 mL

Epson Intelligent Ink Cartridges⁴

In-box Cartridge Fill Volume 110 mL each color x 11 colors

Retail Cartridge Fill Volume 150, 350 or 700 mL each color x 9 colors total

Ink Cartridge Shelf Life 2 years from printed production date or 6 months after opened

Printer is designed for use with Epson cartridges only, not third-party cartridges or ink, www.epson.com/cartridgereturn*

Roll Media Handling

Single Top-loading Roll 44" wide

2" or 3" Core Diameter User-adjustable roll media adapters Roll Cutting⁵ High-speed internal rotary cutter; auto or manual

Minimum Auto Cut Length 5.0" plus top and bottom margin (5.24" min.)

Top/Bottom Margins (mm) Normal: 20/15; option: 35/15, 150/15, 15/15, 3/3

Left/Right margins 3 mm each side; 0.24" total; or 0" at BorderFree® sizes

Roll Paper Remaining Printable barcode tracking system Take-up Reel Auto forward and backward; light-based media

Sheet Media Handling

Single Sheet, Top-loading Up to 44" wide Sheet Loading Auto-loading if less than 0.5 mm thick Media Thickness 0.8 mm to 1.5 mm Top/Bottom Margins 3 mm/15 mm

Top/Bottom Margins with Centering On 15 mm/15 mm Left/Right Margins 3 mm each side; 6 mm or 0.24" total BorderFree Print Widths 10", 11.8", 13", 16", 17", 20.3", 23", 24", 33", 36", 44"

Printable Area and Accuracy

Maximum Paper Width 44"

Minimum Cut-sheet Size 8.5" x 11" Maximum Printable Roll Length⁶ 529"

Line Accuracy +/- 0.2% of specified length (+/- 0.26 mm

Printer Interfaces⁷

Hi-Speed USB 2.0 (1 port) 1000Base-T Ethernet (1 port)

Operating Systems Supported

Apple® OS X® 10.11.x, 10.10.x, 10.9.x, 10.8.x and 10.7.x Windows® 10, 8.1, 7 (32-bit, 64-bit)

General

Weight and Dimensions (W x D x H)

Basket closed: 73.5" x 26.3" x 48" (1864 x 667 x 1218 mm) Weight: 298 lb (135 kg)

Acoustic Noise Level

Less than 47 dB(A) according to ISO 7779

Temperature

Operating: 50 ° to 95 °F (10 ° to 35 °C) Operating (recommended): 65 $^{\circ}$ to 75 $^{\circ}F$ (18 $^{\circ}$ to 24 $^{\circ}C)$ Storage: -4 ° to 104 °F (-20 ° to 40 °C)

Relative Humidity

Operating: 20 - 80% (no condensation)

Operating (recommended): 45 - 60% (no condensation)

Storage: 5 - 85% (no condensation)

Electrical Requirements Voltage: AC 110 - 240 V

Frequency: 50 - 60 Hz Current: 2 A **Power Consumption**

Printing: approx. 75 W Ready: approx. 19 W

Sleep Mode: approx. 2 W (1000 BaseT Ethernet in Standby) Power Off: less than 0.5 W ENERGY STAR® qualified

Standards and Approvals

Safety standards: UL605950-01, CAN/CSA C22.2 No. 60950-1 EMC FCC part 15 subpart B class B, CAN/CSA-CEI/IEC CISPR22 class B.

AS/NZS CISPR 32 class B

Limited Warranty and Service Standard one-year usually next-business day on-site repair with toll-free phone support Monday through Friday

Country of Origin China

*This product uses only genuine Epson-brand cartridges. Other brands of ink cartridges and ink supplies are not compatible and, even if described as compatible, may not function properly

1 lnk lightfastness rating based on accelerated testing of prints on specialty media, displayed indoors, under glass. Actual print stability will vary according to media, printed image, display conditions, light intensity, humidity and atmospheric conditions. Epson does not guarantee longevity of prints. For maximum print life, display all prints under glass or lamination or properly store them. Visit www.wilhelm-research.com for the latest information. | 2 Print times are based upon print engine speeds only. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. Normal is for prints imaged using 1440 x 720 high-speed mode. | 3 Ink used in conversion varies considerably based on temperature and other factors. | 4 Cartridge yields vary considerably based on images printed, print settings, paper type, frequency of use and temperature. For print quality, a variable amount of ink remains in the cartridge after the "replace cartridge" indicator comes on. The printer ships with full cartridges and part of the ink from the first cartridges is used for priming the printer. | 5 High-volume cutting of canvas and heavy media stocks may require frequent cutter replacement. [6 Allowed by printer driver for Mac® and PC. Application, version of application and operating system version may limit maximum length. | 7 For the latest drivers, visit www.epson.com/support

Better Products for a Better Future™

eco.epson.com

SmartWay Transport Partne



Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806 185 Renfrew Drive, Markham, Ontario L3R 6G3

Epson Canada Limited

www.epson.com

EPSON, Epson ESC/P, PrecisionCore, SpectroProofer, SureColor and TEP are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and UltraChrome HDX are trademarks of Seiko Epson Corporation. BorderFree is a registered trademark and Epson Preferred is a service mark of Epson America, Inc. Apple, Mac and OS X are trademarks of Apple Inc. registered in the U.S. and other countries. SmartWay is a service mark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2015 Epson America, Inc. Com-SS-Oct-13 CPD-50255 9/15

Ordering Information	
SureColor P9000 Standard Edition SureColor P9000 Commercial Edition Maintenance Tank Replacement Printer Cutter Blade Additional Roll Media Adapters (pair) Internal Print Server 3206B 44" SpectroProofer® UVS Replacement X-Rite® ILS30EP (for SpectroProofer)	SCP9000SE SCP9000CE T699700 C12C815331 C12C811241 C12C848031 SPECTR044UVS C12C932021
UltraChrome HD Ink (150 mL)	
Photo Black Ink Cartridge Cyan Ink Cartridge Vivid Magenta Ink Cartridge Yellow Ink Cartridge Vivid Light Koartridge Vivid Light Magenta Ink Cartridge Light Black Ink Cartridge Matte Black Ink Cartridge Light Light Black Ink Cartridge UltraChrome HDX Ink (150 mL) Orange Ink Cartridge Green Ink Cartridge	T834100 T834200 T834300 T834400 T834500 T834600 T834700 T834800 T834900
Violet Ink Cartridge	T834D00
UltraChrome HD Ink (350 mL) Photo Black Ink Cartridge Cyan Ink Cartridge Vivid Magenta Ink Cartridge Yellow Ink Cartridge Light Cyan Ink Cartridge Vivid Light Magenta Ink Cartridge Light Black Ink Cartridge Matte Black Ink Cartridge Light Light Black Ink Cartridge	T824100 T824200 T824300 T824400 T824500 T824600 T824700 T824800 T824900

UltraChrome HDX Ink (350 mL)	
Orange Ink Cartridge	T824A00
Green Ink Cartridge	T824B00
Violet Ink Cartridge	T824D00
UltraChrome HD Ink (700 mL)	

Photo Black Ink Cartridge T804100 T804200 Cyan Ink Cartridge Vivid Magenta Ink Cartridge T804300 Yellow Ink Cartridge T804400 Light Cyan Ink Cartridge T804500 Vivid Light Magenta Ink Cartridge T804600 Light Black Ink Cartridge T804700 Matte Black Ink Cartridge T804800 Light Light Black Ink Cartridge T804900

UltraChrome	HDX	Ink	(700	mL)
rango Ink Cartrida	0			

Orange Ink Cartridge T804A00 T804B00 Green Ink Cartridge Violet Ink Cartridge T804D00

Purchase the cartridge size that will most likely be consumed within 6 months of installation in the printer.

Extended Service Plans

One-year Epson PreferredSM Plus Service EPP900B1 Two-year Epson Preferred Plus Service FPP900B2 One-year Epson Preferred Plus SpectroProofer EPPSPB1